

# K 855

## INDUSTRIAL THREE-PHASE DRY VACUUM CLEANERS

Industrial dry vacuum cleaner equipped with a 7.5 hp induction motor. 6-stage turbine with fans of 267 mm diameter. Manual filter shaking system. Fast detachable tank mounted on trolley. HEPA cartridge filter optional. Version "Com. B.T." equipped with 24 V safety voltage. It can be used as a blower. Delivered without accessories, must be ordered separately.



| Lever system | Filter shaker | Waterproof switches |

### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
K 855 HP 7,5 380 V	00-17200101	1
K 855 HP 7,5 Com.B.T.	00-17200121	1

### TECHNICAL DATA

Voltage - Frequency	400 V <sup>3</sup> ~ 50 Hz
Max power rating	W 5500
Rated power (nominal power)	W 5500
Container capacity	l 60
Useful capacity	l 60
Filtering surface	m <sup>2</sup> 1,2
Air flow rate	l/s 135
Vacuum	mbar 300
Sound level	db(A) 70
IP code	IPX4
Power supply cable	m 10
Weight (without accessories)	Kg 120
Dimensions	mm 1200 x 600 x 1300

### STANDARD ACCESSORIES

TYPE	REF. NO.
Textile filter	20-583

Ø 50

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
Flexible hose 3 m	01-510
Reduction 90-50	01-561
PVC extension tube 0,5 m	2512021
Curved suction tube Ø 50	2511700
Adjustable dry brush 0,5 m	6010062
Round brush	2511720
Crevice tool	2511730
PVC reduction Ø 50	2511710
Nylon filter (filtering surface 0,7 m <sup>2</sup> )	20-564
HEPA Cartridge filter (filtering surface 0,9 m <sup>2</sup> )	20-566