# **RANGER** R 115 FD 75 CHEM

#### **RIDE-ON SCRUBBER DRYERS RANGER SERIES**

Ranger R 115 FD 75 is the ride-on scrubber dryer designed for cleaning operations in medium and large areas. It combines high performance and ergonomics along with maximum comfort for the operator. 115 liter capacity and the large cleaning width (750 mm) ensure a productivity of 4500 m<sup>2</sup>/h. The extra down pressure and detergent action (chemical mixing system) ensure excellent cleaning performance; the sturdy aluminium brush head is able to perfectly adapt itself to any obstacle and makes Ranger the ideal machine for cleaning closed to wall. The squeegee, with natural rubber blades supplied as standard, guarantees the best drying performance on every kind of surface. In the event of accidental impacts, the squeegee can also move and automatically retract under the machine frame, guaranteeing maximum safety and effectiveness. The practical and intuitive control panel ensures the control and management of all the machine functions: - it is possible to be immediately ready for the work session thanks the READY TO GO function which allows, by pressing a single button, the activation and setting of all the main functions of the machine; - the ECO SYSTEM program optimizes consumptions and eliminates waste, making Ranger an eco-friendly machine. Ranger is easy to use, no training is required and even daily maintenance operations are guick and easy. That is why even the untrained operators are able to work with this professional scrubber dryer. Available in three versions, one basic and two full package (BC and BC PLUS), with batteries and battery charger included, Ranger can reach up to 7 hours running time in the BC PLUS version!









"Ready to go' function



Chemical mixing system



Extra down pressure



Aluminium hrush head and squeegee group

REF. NO.

10.0715.01 13.0715.01

17 0715 01



access to all the main components

PIECES/PALLET



Immediate opening/ | Manoeuvrability and control



Fronnomics and comfort

#### PRODUCT IDENTIFICATION

TYPE
RANGER R 115 FD 75 CHEM
RANGER R 115 FD 75 BC CHEM
RANGER R 115 FD 75 BC CHEM PLUS

#### **TECHNICAL DATA**

I = OIIIII OA = DAIA		
FEATURES		
Cleaning width	mm	750
Squeegee width	mm	950
Productivity (theoretical - practical)	m²/h	4500 - 2700
Power supply		Battery 24 V
Installed power	W	2300
Advancement		with traction
IP code		IPX3
BATTERIES		
Туре	Gel battery set (4 Pb Wet battery 24	pcs) 6 V 240 Ah (*) - I V 320 Ah (**)
Running time	h - min	5 h (*) - 7 h (**)
Battery compartment dimensions x No	mm x No	380x625x440 X 1
BRUSHES		
Pad diameter x No	mm - inch x No	380 - 15" x 2
Motor rating x No	W x No	500 x 2
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	35;70 - 21;43
TRACTION		
Motor rating	W	600
Driving speed	Km/h	6
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12
VACUUM		
Motor rating	W	550
Vacuum	mbar - mmH <sub>2</sub> 0	125 - 1250
Airflow rating	I/s	30
Noise level	dB(A)	63/57 (***)
TANK		
Type		Double tank
Cleaning solution tank	1	110
Recovery tank		115
Weight (empty/with batteries)	Kg	246 - 432 (*) - 506 (**)
Dimensions	mm	1470x950x1365

## STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
15" Polypropylene brush Ø 0,7 (****)	40.0008.00
Brush Solution Diffuser	96.0207.00
Splashguard	22.0729.00
Set natural rubber squeegee blades (front/rear)	96.0177.00
Gel battery set (4 pcs) 6V 240Ah (*)	22.0718.00
Battery 24V 320Ah (**)	22.0723.00
On board battery charger 24V 30A (*)(**)	18.0089.00
Chemical mixing system	96.0206.00
Blinking kit	96.0181.00

### **OPTIONAL ACCESSORIES**

OI HOMAL ACCESSORIES		
TYPE	REF. NO.	
15" Polypropylene brush Ø 0,9	40.0108.00	
15" Tynex brush Ø 0,9 grit 240	40.0208.00	
Pad holder 355 mm (for 15" pad)	40.1008.00	
Set polyurethane squeegee blades (front + rear)	96.0177.01	
Headlight kit	96.0180.00	
Corner drying kit	96.0182.00	
Water Stop kit	96.0183.00	
Fleet 4 You (*****)	96.0212.00	
Fleet & Key 4 You (*****)	96.0213.00	

(\*) For BC CHEM version

\*) For BC CHEM PLUS version

(\*) Silent mode function

\*) 2 brushes on standard equipment

\*\*\*\*\*) On request and to be defined at time of order