

RAPID 40 D 60

Walk behind scrubber dryers RAPID 40 - with TRACTION

Rapid 40 D 60 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals.

The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment – 40-litre tank capacity, three-hour running time, interactive control panel, double brush pressure, “silent mode” function, the new chemical mixing system – make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The wide cleaning path (2 x 12” brushes) and the adjustable speed (up to 5 km/h) allow a productivity of up to 3050 m²/h. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, Wirbel’s patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive!



Product identification

Type	Ref. No.	Pieces/pallet
RAPID 40 D 60 TOUCH	10.4293.01	1
RAPID 40 D 60 BC CHEM TOUCH	17.4293.01	1



- | | |
|--|-----------------------------------|
| 1 Control panel | 5 Adjustable and compact squeegee |
| 2 Password for reliability and ease of use | 6 Debris tray + vacuum filter |
| 3 Touch System | 7 Chemical mixing system |
| 4 “Built in” solution tank filter | |

Technical data

Features		
Cleaning width	mm	600
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	3050 - 1830
Power supply		Battery 24V
Installed power	W	1190
Advancement		With traction
IP code		IPX3
Batteries		
Type	Gel battery set (2 pcs) 12 V 105 Ah (*)	
Running time	h - min	2 h and 30 min
Battery compartment dimensions x No	mm x No	340x340x285 X 1
Brushes		
Pad diameter x No	mm - inch x No	310 - 12” x 2
Motor rating x No	W x No	450 x 1
Motor speed	rpm	200
Down pressure - Contact pressure	Kg - g/cm ²	27 - 27 ; 32 - 32
Traction		
Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2
Vacuum		
Motor rating	W	550
Vacuum	mbar - mmH ₂ O	1250
Airflow rating	l/s	30
Noise level	dB(A)	63/57 (**)
Tank		
Type	Double tank	
Cleaning solution tank	l	40
Recovery tank	l	42
Weight (empty/with batteries)	Kg	116 / 196
Dimensions	mm	1125x670x1040

Standard Accessories

Type	Ref. No.
Solution tank filling hose	30.0024.00
12” Polypropylene brush Ø 0.7 (***)	40.0001.00
Detachable brush deck splash guard (without bristles)	24.0266.00
Brush deck splash guard bristles	40.4007.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)(****)	96.0171.00
Gel battery set (2 pcs) 12 V 105 Ah (*)	18.0001.00
On board charger 24 V 9 A (*)	22.0623.00
Chemical mixing system (*)	96.0048.00

Optional Accessories

Type	Ref. No.
12” Polypropylene brush Ø 0.9	40.0101.00
12” Polypropylene brush Ø 1.2	40.0301.00
12” Tynex brush Ø 1.2 grit 80	40.0201.00
Pad holder 290 mm (for 12” pad)	40.1001.00
Set front + rear polyurethane squeegee blades	96.0055.00

(*) For BC CHEM version
 (**) Silent mode function
 (***) 2 on standard equipment
 (****) It is possible to use maximum two weights until you reach 1400 g of total additional weight