## **RAPID 40 M 55**



# WALK BEHIND SCRUBBER DRYERS RAPID 40 - MANUAL

Rapid 40 M 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment — 40-litre tank capacity, interactive control panel, double brush pressure, "silent mode" function, the new chemical mixing system— make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 M 55 TOUCH with a finger has never been so practical and intuitive!





Control panel



Password for reliability and ease of use



Touch System



"Built in" solution tank filter



Adjustable squeegee



Compact squeegee



Debris tray + vacuum filter



Chemical mixing system

#### PRODUCT IDENTIFICATION

PRODUCT IDENTIFICATION			
TYPE	REF. NO.	PIECES/PALLET	
RAPID 40 M 55 TOUCH	10.4291.01	1	
RAPID 40 M 55 BC CHEM TOUCH	17.4291.01	1	

#### **TECHNICAL DATA**

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m²/h	2120 - 1270
Power supply		Battery 24V
Installed power	W	1060
Advancement		Manual
IP code		IPX3
BATTERIES		
Туре	Gel battery set (2 pcs) 12 V 76 Ah (**)	
Running time	h - min	1 h and 30 min
Battery compartment dimensions x No	mm x No	340x340x285 X 1
BRUSHES		
Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	25,5 - 16,5 ; 30,5 - 19,7
TRACTION		
Motor rating	W	
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2
VACUUM		
Motor rating	W	550
Vacuum	mbar - mmH <sub>2</sub> 0	1250
Airflow rating	I/s	30
Noise level	dB(A)	63/57*

TANK		
Type		Double tank
Cleaning solution tank	I	40
Recovery tank	I	42
Weight (empty/with batteries)	Kg	90,5 / 143,5
Dimensions	mm	1210x560x1040

### **STANDARD ACCESSORIES**

STANDAND ACCESSORIES	
TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24 V 9 A (**)	22.0623.00
Gel battery set (2 pcs) 12 V 76 Ah (**)	18.0000.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck splash guard bristles	40.4003.00
Set front+rear natural rubber squeegee blades	96.0091.01
Chemical mixing system (**)	96.0048.00
Extra weight for squeegee (1x700 g) (***)	96.0171.00

#### **OPTIONAL ACCESSORIES**

OF FIGURE ACCEPTABLE				
REF. NO.				
40.0103.00				
40.0303.00				
40.0203.00				
40.1003.00				
96.0055.00				
96.0171.00				

<sup>(\*)</sup> Silent mode function

<sup>(\*\*)</sup> For BC CHEM version

<sup>(\*\*\*)</sup> It is possible to use maximum two weights until you reach 1400 g of total additional weight