

RAPID 40 M 55

PATENTED

WALK BEHIND SCRUBBER DRYERS RAPID 40 - MANUAL

Rapid 40 M 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment – 40-litre tank capacity, interactive control panel, double brush pressure, “silent mode” function, the new chemical mixing system – make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 M 55 TOUCH with a finger has never been so practical and intuitive!



Control panel



Password for reliability and ease of use



Touch System



“Built in” solution tank filter



Adjustable squeegee



Compact squeegee



Debris tray + vacuum filter



Chemical mixing system

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 M 55 TOUCH	10.4291.01	1
RAPID 40 M 55 BC CHEM TOUCH	17.4291.01	1

TECHNICAL DATA

FEATURES			
Cleaning width	mm	530	
Squeegee width	mm	750	
Productivity (theoretical - practical)	m ² /h	2120 - 1270	
Power supply		Battery 24V	
Installed power	W	1060	
Advancement		Manual	
IP code		IPX3	
BATTERIES			
Type		Gel battery set (2 pcs) 12 V 76 Ah (*)	
Running time	h - min	1 h and 30 min	
Battery compartment dimensions x No	mm x No	340x340x285 X 1	
BRUSHES			
Pad diameter x No	mm - inch x No	530 - 21" x 1	
Motor rating x No	W x No	500 x 1	
Motor speed	rpm	165	
Down pressure - Contact pressure	Kg - g/cm ²	25,5 - 16,5 ; 30,5 - 19,7	
TRACTION			
Motor rating	W	---	
Driving speed	Km/h	4	
Hill climbing ability (full load)	%	2	
VACUUM			
Motor rating	W	550	
Vacuum	mbar - mmH ₂ O	1250	
Airflow rating	l/s	30	
Noise level	dB(A)	63/57 (**)	
TANK			
Type		Double tank	
Cleaning solution tank	l	40	
Recovery tank	l	42	
Weight (empty/with batteries)	Kg	90,5 / 143,5	
Dimensions	mm	1210x560x1040	

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck splash guard bristles	40.4003.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)	96.0171.00
Gel battery set (2 pcs) 12 V 76 Ah (*)	18.0000.00
On board charger 24 V 9 A (*)	22.0623.00
Chemical mixing system (*)	96.0048.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" polypropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00
Extra weight for squeegee (1x700 g) (***)	96.0171.00
Fleet 4 You (****)	96.0212.00
Fleet & Key 4 You (****)	96.0213.00

(*) For BC CHEM version

(**) Silent mode function

(***) It is possible to use maximum two weights until you reach 1400 g of total additional weight

(****) On request and to be defined at time of order