

RAPID 40 M 55

PATENTED

WALK BEHIND SCRUBBER DRYERS RAPID 40 - MANUAL

Rapid 40 M 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment – 40-litre tank capacity, interactive control panel, double brush pressure, “silent mode” function, the new chemical mixing system – make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 M 55 TOUCH with a finger has never been so practical and intuitive!




Control panel



Password for reliability and ease of use



Touch System



“Built in” solution tank filter



Adjustable squeegee



Compact squeegee



Debris tray + vacuum filter



Chemical mixing system

PRODUCT IDENTIFICATION

TYPE

RAPID 40 M 55 TOUCH

RAPID 40 M 55 BC CHEM TOUCH

REF. NO.

10.4291.01

17.4291.01

PIECES/PALLET

1

1

TECHNICAL DATA

FEATURES

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	2120 - 1270
Power supply		Battery 24V
Installed power	W	1060
Advancement		Manual
IP code		IPX3

BATTERIES

Type	Gel battery set (2 pcs) 12 V 76 Ah (*)
Running time	h - min 1 h and 30 min
Battery compartment dimensions x No	mm x No 340x340x285 X 1

BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm ²	25,5 - 16,5 ; 30,5 - 19,7

TRACTION

Motor rating	W	---
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2

VACUUM

Motor rating	W	550
Vacuum	mbar - mmH ₂ O	1250
Airflow rating	l/s	30
Noise level	dB(A)	63/57 (**)

TANK

Type		Double tank
Cleaning solution tank	l	40
Recovery tank	l	42
Weight (empty/with batteries)	Kg	90,5 / 143,5
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

TYPE

REF. NO.

Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck splash guard bristles	40.4003.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)	96.0171.00
Gel battery set (2 pcs) 12 V 76 Ah (*)	18.0000.00
On board charger 24 V 9 A (*)	22.0623.00
Chemical mixing system (*)	96.0048.00

OPTIONAL ACCESSORIES

TYPE

REF. NO.

21" polypropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00
Extra weight for squeegee (1x700 g) (***)	96.0171.00
Fleet 4 You (****)	96.0212.00
Fleet & Key 4 You (****)	96.0213.00

(*) For BC CHEM version

(**) Silent mode function

(***) It is possible to use maximum two weights until you reach 1400 g of total additional weight

(****) On request and to be defined at time of order