

RAPID 40 SD 55

Walk behind scrubber dryers RAPID 40 - with TRACTION

Rapid 40 SD 55 TOUCH is the scrubber dryer which has been specifically conceived for daily use.


The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Cutting edge features and technical equipment make RAPID 40 SD an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The SD version introduces itself with top-notch innovations.

- **Simply Driven:** a solutions system which is able to combine the best scrubbing and drying performance with an extreme driveability and ease of use: the result is a perfect mix between practicality and cost-effectiveness which guarantees the best operational performance.
- **TOUCH SYSTEM:** the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive! RAPID 40 SD 55 TOUCH is available in three versions: one basic and two full-package which includes batteries and a battery charger (up to 2 hours and 45 minutes running time for the BC PLUS version).



Product identification

Type	Ref. No.	Pieces/pallet
RAPID 40 SD 55 TOUCH	10.4232.01	1
RAPID 40 SD 55 BC TOUCH	13.4232.01	1
RAPID 40 SD 55 BC PLUS TOUCH	15.4232.01	1



- 1 Control panel
- 2 Touch System
- 3 "Built in" solution tank filter
- 4 Debris tray + vacuum filter
- 5 Adjustable and compact squeegee

Technical data

Features		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	2650 - 1590
Power supply		Battery 24V
Installed power	W	1090
Advancement		with traction
IP code		IPX3
Batteries		
Type	Gel battery set (2 pcs) 12 V 76 Ah (*) - Gel battery set (2 pcs) 12 V 105 Ah (**)	
Running time	h - min	1 h and 30 min (*) - 2 h and 45 min (**)
Battery compartment dimensions x No	mm x No	340x340x285 X 1
Brushes		
Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	350 x 1
Motor speed	rpm	115
Down pressure - Contact pressure	Kg - g/cm ²	25,5 - 16,5
Traction		
Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2
Vacuum		
Motor rating	W	550
Vacuum	mbar - mmH ₂ O	1791
Airflow rating	l/s	30
Noise level	dB(A)	63
Tank		
Type		Double tank
Cleaning solution tank	l	40
Recovery tank	l	42
Weight (empty/with batteries)	Kg	109 / 189
Dimensions	mm	1210x560x1040

Standard Accessories

Type	Ref. No.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)(****)	96.0171.00
Gel battery set (2 pcs) 12 V 76 Ah (*)	18.0000.00
Gel battery set (2 pcs) 12 V 105 Ah (**)	18.0001.00
On board charger 24 V 9 A (*) (**)	22.0623.00

Optional Accessories

Type	Ref. No.
21" Polypropylene brush Ø 0.9	40.0103.00
21" Polypropylene brush Ø 1.2	40.0303.00
21" Tynex brush Ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0055.00

(*) For BC version
 (**) For BC PLUS version
 (***) 2 on standard equipment
 (****) It is possible to use maximum two weights until you reach 1400 g of total additional weight