

ROLLY NRG 7½ E 33

PATENTED

COMPACT WALK BEHIND SCRUBBER DRYERS ROLLY NRG SERIES

NRG, New Rolly Generation, is the new Rolly compact scrubber dryer, even more performing and reliable for top cleaning results! NRG such as energy, power, but also innovation: an integrated system of technical solutions able to meet the needs of the most demanding cleaning professionals. Comfort in narrow spaces, where no one arrives: - 7,5 liters of tank capacity, its dimensions, combined with a special handle (patented) and swivel wheels allow Rolly to go and work in small areas. Top cleaning and drying results: - the cylindrical brush deck, with three different down pressure adjustable by knob, against every kind of dirt; - an unbelievable alternate twin squeegee system (patented), for top drying results and optimized consumptions at the same time; - low noise level (only 54 dbA), perfect for day cleaning and in all the environments (hospitals, resthomes, schools...) where silence is a must. A start & go machine: No training required, everybody can use Rolly: - all the main functions can be managed by the intuitive control panel; - coloured levers and knobs clearly help the user preparing the machine for work or while using it; - effortless maintenance. Rolly 7 ½ E 33 is the electric version with a standard power supply kit case and a 15 meters cable.




Ergonomic handle with unlocking system



Adjustable down pressure by knob (3 steps)



Power supply kit case



Alternate twin squeegee system (patented)



Compact dimensions to go and work where no one arrives



Fast and easy maintenance



Easy to transport, park, store

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROLLY NRG 7½ E 33	10.6075.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	330
Squeegee width	mm	420
Productivity (theoretical - practical)	m²/h	1320 - 800
Power supply		Cable 230 V - 50 Hz
Installed power	W	270
Advancement		Manual
IP code		IPX3
BRUSHES		
Pad diameter x No	mm - inch x No	80 - Cyl. x 1
Motor rating x No	W x No	120 x 1
Motor speed	rpm	800
Contact pressure	g/cm²	35 - 71 - 160
TRACTION		
Motor rating	W	---
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2
VACUUM		
Motor rating	W	150
Vacuum	mbar - mmH ₂ O	48 - 490
Airflow rating	l/s	30
Noise level	dB(A)	58 / 54 *
TANK		
Type		Double tank
Cleaning solution tank	l	7,5
Recovery tank	l	8
Weight (empty/with batteries)	Kg	23/25,5
Power supply cable	m	15
Dimensions	mm	640x450x422

STANDARD ACCESSORIES

TYPE	REF. NO.
Polypropylene cylindrical blue brush	40.5000.00
Brush Solution Diffuser	40.5000.05
Set front/rear polyurethane squeegee blade	96.0084.00
Set front/rear rubber squeegee blade	96.0085.00
Kit case power supply 230V	22.0509.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Soft cylindrical polypropylene brush	40.5000.01
Hard cylindrical polypropylene brush	40.5000.02
Tynex cylindrical brush grit 360	40.5000.03
Tynex cylindrical brush grit 80	40.5000.08
Case batteries Lithium 24V 280Wh	22.0508.00
Case batteries Lithium 24V 560Wh	22.0508.01
24V 5A charger	22.0619.00
24V 10A charger	22.0619.01
Car charger 24-12V 3A	18.0065.00

(*) Silent mode function